




Macan 4

2026



Your dream becomes reality

Porsche Code: PTRJYTF9



Visit the following link to view your configuration: <https://porsche-code.com/PTRJYTF9>

 4/22/2026


Exterior Colours & Wheels

Category	Option	Option code	Price
Exterior Colour	 White	0Q	
Wheels	 20-inch Macan Wheels	54N	Standard Equipment
Tyres	Summer tyres for 20-inch wheels	J46	Standard Equipment


Interior Colours & Seats

Category	Option	Option code	Price
Interior Colours & Materials	 Leather Package Black/Crayon	PO	
Seats	 Adaptive sports seats in front (18-way, electric)	Q1J	

Interior

Category	Option	Option code	Price
Seatbelts & Seat Design	 'PORSCHE' logo front seats, illuminated	NR2	

Technology

Category	Option	Option code	Price
Powertrain & Performance	 Single-Speed transmission	G1Z	Standard Equipment

Others

Category	Option	Option code	Price
Others	TPM Valve in Black	UX7	Standard Equipment

Standard Equipment

Wheels

- 20-inch Macan Wheels

Wheel Colours

- Wheel centre caps with monochrome Porsche crest

Tyres

- Summer tyres for 20-inch wheels

Wheel Accessories

- Anti-theft wheel bolts
- Tyre Pressure Monitoring System (TPM)

Seats

- Comfort seats front (8-way, electric)
- 4+1 seats
- Seat heating (front)
- ISOFIX/I-Size mounting points on outer rear seats

Equipment Packages

- Equipment 'base'
- Standard equipment

Exterior design

- Sideskirts
- Exterior mirror lower trims including mirror base in Black
- Side window trims Black (satin-gloss)
- Door handles painted in exterior colour
- Automatic tailgate
- Body shape SUV
- Pedestrian safety

Roof & transport systems

- Aluminium roof
- Preparation for towbar system
- Without roof rails

Lettering & decals

- Model designation Silver coloured
- Sideblades Lava Black with 3D texture

Powertrain & Performance

- Performance Battery Plus
- Porsche E-Performance Powertrain with a permanent magnet synchronous motor on the front and rear axle
- Power Steering
- Four-wheel drive
- Steel Spring Suspension
- Brake system with brake calipers in Black
- Single-Speed transmission

Lights & Vision

- LED main headlights
- LED taillights with 'PORSCHE' lettering
- Electric folding exterior mirrors
- Interior mirror dimmed manually
- Windscreen in thermally insulated glass

Interior packages & decors/materials

- Interior Package Black (high-gloss)
- Accent Package Silvershade

Seatbelts & Seat Design

- Seat belts Black
- Head rests
- Reversible seatbelt pretensioner

Steering wheel, gearshift/selector lever

- Multifunction Steering Wheel in Leather with Mode-Switch
- Steering wheel with manual fore/aft and height adjustment

Interior design

- Fabric roof lining
- Sun visors for driver and front passenger
- Pedals and footrest in Black
- Door sill guards in aluminium with model designation

Keys, mats & wallets

- Floor mats front and rear

Assistance systems

- ParkAssist (front and rear) including reversing camera
- Traffic sign recognition
- Lane Change Assist
- Lane Keeping Assist including emergency stop function
- Intersection Assist
- Cruise control
- Warn and Brake Assist
- Swerve and Turn Assist
- Emergency call systems eCall and bCall
- Driver Awareness Detection

Comfort & everyday usability

- Two-zone automatic climate control
- Particle/pollen filter with active carbon filter
- Ambient and communication lighting
- Alarm system with interior surveillance
- Non-smoking package
- Alcohol Interlock preparation
- Side airbags and centre airbag in the front
- Airbags
- Keyless Drive
- First Aid Kit with warning triangle

Infotainment

- Smartphone compartment with wireless charging (up to 15W)
- Digital radio
- Sound Package Plus

Charging & Range

- Acoustic Vehicle Alerting System (AVAS)
- Heat Pump
- On-Board AC Charger with up to 11 kW charging power
- Charging cable for charging at alternating current chargers with 6 m length (up to 11 kW)
- Manual Charging Cover

Others

- TPM Valve in Black

Technical Data

Power unit

Power up to (kW)	285 kW
Power up to (PS)	387 PS
Overboost Power with Launch Control up to (kW)	300 kW
Overboost Power with Launch Control up to (PS)	408 PS
Max. torque with Launch Control up to	650 Nm

Performance

Top speed	220 km/h
Acceleration 0 - 100 km/h with Launch Control	5.2 s
Acceleration 0 - 160 km/h with Launch Control	11.8 s
Acceleration 0 - 200 km/h with Launch Control	19.0 s
Acceleration (80-120km/h) (50-75 mph) with Launch Control	3.1 s

Range

Electric range combined (model range)	527 - 610 km
Electric range city (model range)	675 - 776 km
Electric range combined (ECE)	619 km

Charging

Gross battery energy content	100.0 kWh
Maximum charging power with direct current (DC)	270 kW
Charging time for alternating current (AC) with 9.6 kW (0 to up to 100 %)	11.50 h
Charging time for alternating current (AC) with 11 kW (0 to up to 100 %)	10.00 h
Charging time for alternating current (AC) with 19.2 kW (0 to up to 100 %)	5.75 h
Charging time for alternating current (AC) with 22 kW (0 to up to 100 %)	5.25 h
Charging time for Direct Current (DC) with 400 V infrastructure (10-80%)	33 min
Charging time for direct current (DC) with maximum charging power (10 to up to 80 %)	21 min
Recharged range (WLTP) in 10 min with 150 kW	123 km
Recharged range (WLTP) in 10 min with maximum DC charging power	249 km

Consumption/Emissions WLTP

Electric energy consumption combined (model range)	20.4 - 17.8 kWh/100 km
Electric energy consumption city (model range)	15.9 - 13.9 kWh/100 km
Electric energy consumption low (model range)	15.3 - 13.5 kWh/100 km
Electric energy consumption medium (model range)	16.3 - 14.2 kWh/100 km
Electric energy consumption high (model range)	18.7 - 16.2 kWh/100 km
Electric energy consumption extra-high (model range)	26.3 - 22.9 kWh/100 km
CO ₂ -emissions combined (model range)	0 - 0 g/km

Consumption/Emissions (ECE)

Electrical consumption combined	170 Wh/km
---------------------------------	-----------

Sound level (type approved based on UN-R 51)

Sound level of passing vehicle

67 dB(A)

Body

Length	4,784 mm
Width	1,938 mm
Width (with mirrors)	2,152 mm
Width (with mirrors folded)	1,954 mm
Height, steel suspension (DIN)	1,624 mm
Height with roof rails, steel suspension (DIN)	1,633 mm
Height, steel suspension (PASM DIN)	1,624 mm
Height with roof rails, steel suspension (PASM DIN)	1,633 mm
Height, steel suspension (EC)	1,618 mm
Height with roof rails, steel suspension (EC)	1,628 mm
Height, air suspension (standard level)	1,623 mm
Height with roof rails, air suspension (standard level)	1,633 mm
Height, air suspension (off-road level)	1,643 mm
Height with roof rails, air suspension (off-road level)	1,653 mm
Height, air suspension (extra off-road level)	1,663 mm
Height with roof rails, air suspension (extra off-road level)	1,673 mm
Height, air suspension (low level)	1,608 mm
Height with roof rails, air suspension (low level)	1,618 mm
Height, air suspension (extra-low level)	1,593 mm
Wheelbase	2,893 mm
Turning circle	12.1 m
Unladen weight (DIN)	2,330 kg
Unladen weight (EU)	2,405 kg
Permissible gross weight	2,920 kg
Maximum load	590 kg
Nose weight (EG)	100 kg
Max. towing load (braked)	2,500 kg

Max. towing load (unbraked) 750 kg

Maximum permissible roof load with Porsche roof transport system 75 kg

Terrain features

Overhang front/rear	945 - 946 mm
Loading sill height, steel suspension (DIN)	786 mm
Max. ground clearance, steel suspension (DIN)	186 mm
Max. clearance between ground and water-sensitive parts, steel suspension (DIN)	300 mm
Breakover angle, steel suspension (DIN)	14.9 °
Approach/departure angle, steel suspension (DIN)	12.6 - 20.9 °
Max. ground clearance, steel suspension (PASM DIN)	186 mm
Max. clearance between ground and water-sensitive parts, steel suspension (PASM DIN)	300 mm
Breakover angle, steel suspension (PASM DIN)	14.9 °
Approach/departure angle, steel suspension (PASM DIN)	12.6 - 20.9 °
Max. ground clearance, steel suspension (EC)	180 mm
Max. clearance between ground and water-sensitive parts, steel suspension (EC)	300 mm
Breakover angle, steel suspension (EC)	14.5 °
Max. ground clearance, air suspension (normal ride height)	185 mm
Max. clearance between ground and water-sensitive parts, air suspension (standard level)	300 mm
Approach/departure angle, air suspension (standard level)	12.8 - 20.7 °
Breakover angle, air suspension (standard level)	15.0 °
Max. ground clearance, air suspension (off-road level)	205 mm
Max. clearance between ground and water-sensitive parts, air suspension (off-road level)	320 mm
Breakover angle, air suspension (off-road level)	16.6 °
Max. ground clearance, air suspension (extra off-road level)	225 mm
Max. clearance between ground and water-sensitive parts air suspension (extra off-road level)	340 mm
Breakover angle, air suspension (extra off-road level)	18.2 °
Approach/departure angle, air suspension (extra off-road level)	15.4 - 24.0 °

Max. ground clearance, air suspension (low level)	170 mm
---	--------

Breakover angle, air suspension (low level)	13.7 °
---	--------

Capacities

Luggage compartment volume, front	84 l
-----------------------------------	------

Open luggage compartment volume (up to the upper edge of the rear seats)	540 l
--	-------

Largest luggage compartment volume (behind front seats, up to roof)	1,348 l
---	---------





